

		DuraVigo-150
<b>Hardness methods</b>	Rockwell & Superficial Rockwell	ISO 6508 ASTM E18 JIS Z 2245
	Brinell Depth (HBT)	Not standardized. Calibration table required.
	Carbon hardness	DIN 51917
	Ball indentation hardness	ISO 2039
<b>Force range</b>		29.4 - 2452 N (3-250 kgf)
<b>Test force</b>	Force application	Fully automatic, closed loop, force feedback, loading, dwell, unloading
	Test force tolerance	< 0.5 %
	Dwell time settings	Adjustable 1 to 99 s
<b>Conversion</b>		Conversions to other hardness methods according to ASTM E140,, ISO 18265, GB/T 1172
<b>Turret</b>	1 Position	1
<b>Electrical data</b>	Power supply	100 V AC - 240 V AC, 50/60Hz, single phase
	Power consumption max. work load	100 W
	Power consumption idle	13 W
	Power consumption max. load	100 W
	Power inlet	1-phase (N+L1+PE) or 2-phase (L1+L2+PE) The electrical installation must comply with Installation Category II
<b>Residual Current Circuit Breaker (RCCB)</b>		Type A, 30 mA is required depending on local regulations.
<b>Dimensions</b>	Width	230 mm (9.1")
	Depth	550 mm (21.7")
	Height	855 mm (33.7")
<b>Weight</b>		115 kg (252 lbs)
<b>Read method</b>		Automated
<b>Measurement camera resolution</b>		NA
<b>Positions in nosepiece</b>		1
<b>Position in nosepiece for overview camera</b>		
<b>Max no. of indenters</b>		1
<b>Max no. of objectives</b>		NA



		DuraVigo-150
<b>Indenter Shaft</b>	Diameter	6.35
<b>Standard objectives included</b>		NA
<b>Z-Axis</b>		Manual
<b>Anti-collision protection</b>		
<b>XY Stage / Anvil</b>		Anvil, Ø60 mm (2.4"), other sizes and shapes optional
<b>Stage Illumination</b>		Yes
<b>Software</b>	Operating software	Embedded
	Integrated PC	No
	Monitor	6.5" portrait mode capacitive touch screen
	Dual view	No
	Possibility to connect printer	No
	Ethernet Connection	No
	Data Export	USB
<b>System</b>	Data output	TXT
<b>Software modules</b>		Total test, max, min, average, range, standard deviation, all in real time after each test
<b>Sample height</b>		240 mm (9.4")
<b>Throat depth</b>		150 mm (5.9")
<b>Safety standards</b>		CE labeled according to EU directives
<b>REACH</b>		For information about REACH. contact your local Struers office
<b>Operating environment</b>	Surrounding temperature	10 - 35°C (50 - 95°F)
	Humidity	10% - 90% RH non-condensing
<b>Safety Circuit Categories/Performance Level</b>	Emergency stop	EN ISO 13849-1 PL c, Category 1 Stop category 0
<b>Noise level</b>	A-weighted sound emission pressure level at workstations	< 70 dB(A)
<b>Vibration level</b>	During operation	Total vibration exposure to upper parts of the body does not exceed 2.5 m/s <sup>2</sup> .